

T71FC AND T72FC ROTARY STEERING SYSTEMS



**FEATURING
PLANETARY GEAR
DESIGN**

A COMPLETE STEERING SYSTEM CONSISTS OF:

- Steering helm:
 - T71FC - 38867 H - single cable steering helm
 - T72FC - 38868 K - dual cable steering helm
- Mounting bezel:
 - X34 - 36654 B - black, 90° mounting
 - X34W - 40654 C - white, 90° mounting
 - X35 - 36655 C - black, 20° mounting
- Steering cable: **M66**
NOTE: two M66 are needed with the T72FC system
- Optional steering wheel (see index)
- Engine connection kits (see index)

FEATURES AND TECHNICAL SPECIFICATIONS:

- Fast connect, simple installation
 - All stainless steel cable output ends
 - Corrosion resistant materials
 - Particularily suitable where clearance is limited
 - Optional 90° or 20° installation
 - Standard 3/4" tapered shaft
 - Lock-to-lock steering wheel turns: approx. 3,8
 - Stroke: 228 mm (9")
 - Maximum allowable steering wheel diameter: 406 mm (16")
 - Minimum steering cable bend radius: 200 mm (7.9")
 - Minimal feedback
 - Compact for mounting
 - T71FC and T72FC steering systems are not to be used on boats equipped with engines that exceed the maximum horsepower rating of the boat
 - For boats faster than 50 mph our hydraulic steering systems are recommended
 - T71FC steering system is also available in package with ROTECH-I
- Exceeds EN 28848 safety standards
 - Exceeds ABYC P17 safety standards

