

RAVENOL Fork Oil Ultra Light 2,5W

RAVENOL Fork Oil Ultra Light 2,5W is a fully synthetic fork oil on ester base which was developed for all forks of high performance motorbikes and especially for SHOWA and USD forks. The synthetic components and the excellent viscosity index of RAVENOL Fork Oil Ultra Light 2,5W offer an optimum damping behaviour at all temperatures as well as an excellent air separation behaviour under all operating conditions – even during racings.

Application Notes:

RAVENOL Fork Oil Ultra Light 2,5W was developed for the use in all chassis components of two-wheeler vehicles and offers excellent power characteristics. In order to obtain the optimum viscosity for the vehicle and operating condition the fully synthetic fork oils are miscible among each other.

Quality Classifications:

Practice and tested in aggregates with filling

Aprilia, BMW, Ducati, Honda, Kawasaki, Moto-Guzzi, Suzuki, Triumph, Yamaha

Characteristic:

RAVENOL Fork Oil Ultra Light 2,5W offers:

· good damping characteristics at all temperatures

- · a high and stable viscosity index
- an excellent protection against corrosion, therefore a longer endurance of the fork components
- as far as possible protection against corrosion of the inside components
- a very good air and water separation behaviour to prevent foam formation
- neutral behaviour against sealings made of plastics

· a very low pour point

Unit	Data	Audit	
	klar, grün	-	
kg/m³	867	EN ISO 12185	
mm²/s	19,8	DIN 51 562	
mm²/s	6,5	DIN 51 562	
°C	150	DIN ISO 2592	
°C	<-47	DIN ISO 3016	
	kg/m³ mm²/s mm²/s °C	kg/m³ klar, grün kg/m³ 867 mm²/s 19,8 mm²/s 6,5 °C 150	kg/m³ kg/m³ 867 EN ISO 12185 mm²/s 19,8 DIN 51 562 mm²/s 6,5 DIN 51 562 °C 150 DIN ISO 2592

All indicated data are approximate values and are subject to the commercial fluctuations.

All information correspond to the best of our knowledge to the actual situation of the cognitions and our development. Subject to alterations. All references made to DIN-norms are only for the description of the goods. There is no guarantee. In case there will be any problems please contact the technical service.

29.10.2014

Ravensberger Schmierstoffvertrieb GmbH Postfach 1163 33819 Werther Tel.: 05203/9719-0 Fax.: 052039719-40 / 41