



## RAVENOL Fork Oil Medium 10W

RAVENOL Fork Oil Medium 10W is a fork oil on mineral oil base which was developed for all forks of off-road motorbikes and motor cross bikes.

RAVENOL Fork Oil Medium 10W is especially characterised by a high and stable viscosity index as well as a solid corrosion protection. Efficient additives offer even under extreme loads an excellent corrosion protection. The behaviour against sealing materials is neutral.

### Application Notes:

RAVENOL Fork Oil Medium 10W was developed for the use in all chassis components of two-wheeler vehicles and offers good power characteristics. In order to obtain the optimum viscosity for the vehicle and operating condition the mineral fork oils are miscible among each other.

### Quality Classifications:

RAVENOL Fork Oil Medium 10W is practice-related and tested for the use in aggregates of:

#### Practice and tested in aggregates with filling

Suzuki, Yamaha, Kawasaki, Honda, Aprilia, BMW, Ducati, Triumph, Moto-Guzzi

### Characteristic:

RAVENOL Fork Oil Medium 10W offers:

- good damping characteristics at all temperatures
- a high and stable viscosity index
- an excellent protection against corrosion, therefore a longer endurance of the fork components
- as far as possible protection against corrosion of the inside components
- a very good air and water separation behaviour to prevent foam formation
- neutral behaviour against sealings made of plastics
- a very low pour point

Characteristics	Unit	Data	Audit
Colour		yellow	visual
Density at 15°C	kg/m <sup>3</sup>	860	EN ISO 12185
Viscosity at 40°C	mm <sup>2</sup> /s	33,0	DIN 51 562
Viscosity at 100°C	mm <sup>2</sup> /s	6,6	DIN 51 562
Viscosity index VI		>160	DIN ISO 2909
Flash point (COC)	°C	>180	DIN ISO 2592
Pourpoint	°C	-45	DIN ISO 3016
TBN	mg KOH/g	0,4	DIN ISO 3771
Sulphated ash	%wt.	ca. 0,06	-

All indicated data are approximate values and are subject to the commercial fluctuations.

All information correspond to the best of our knowledge to the actual situation of the cognitions and our development. Subject to alterations. All references made to DIN-norms are only for the description of the goods. There is no guarantee. In case there will be any problems please contact the technical service.

26.11.2014

Ravensberger Schmierstoffvertrieb GmbH

Postfach 1163

33819 Werther

Tel.: 05203/9719-0

Fax.: 052039719-40 / 41