


# TECHNICAL DATA SHEET



Type no.	955 51	
Article no.	010955510101	
Standards	DIN EN 50342-1, 50342-2	
Application	Long-term discharge battery	
<b>Electrical data</b>		
Rated voltage	12V	
Rated capacity	55 Ah(K5), 72 Ah(K20), 85 Ah(K100)	
<b>Dimensions and weights</b>		
Box	MO60	
Length max.	256mm	
Width max.	174mm	
Box height max.	205mm	
Total height max.	205mm	
Battery weight	Ca. 20,0 kg (+/- 5 %)	
Electrolyte density	Approx. 1,28 kg/l	
Electrolyte	Diluted sulphuric acid	
Items/pallet	51	
Pallet ID	Euro pallet	
Items per layer	17	
<b>Features</b>		
Base hold-down	B00	
Layout	1	
Terminal	1	
Separator	PE bag separator with glass nonwoven	
Degassing	Battery with central degassing	
Flame arrester	Integrated	
<b>Maintenance 1)</b>		
Water consumption	> 4g/Ah	
Refill water	Distilled or demineralised (DIN 43530)	
Self-discharge	Approx. 9 % per month	
Charging current	Approx. 1/10 of the rated capacity	
Charging voltage 2)	max. 14,4 V	

1) All the listed values relate to room temperature +25° C

2) Recommendation with an external, voltage-regulated charge

1 Document DBTBAT00339 prepared on 2017-04-28 ; Rights relating to changes and errors retained.  
original