

TECHNICAL DATA SHEET

Crepe masking tape

Art. no. 0992 001 5

P. Qty.: 20

General masking tasks in the vehicle and painting fields, for example, on painted metal, glass, chrome parts and rubber.



Adhesive base	Natural rubber
Adhesive tape backing material	Paper
Colour (Color)	Cream
Width	15 mm
Length	50 m
Thickness	130 µm
Elongation at break	10 %
Min./max. processing temperature	5 to 40 °C
Max. temperature resistance	80 °C
Ultraviolet resistance	No
Moisture resistance	Yes
Shelf life from production/conditions	12 Month/at 20 °C and 50% humidity

Application area

General masking tasks in the vehicle and painting fields, e.g. on painted metal, glass, chrome parts, rubber.
Masking for painting work, securing masking paper.

Notice

To ensure residue-free removal, the tape must be removed immediately after the paint or varnish has dried.
The adhesive tape is not UV-resistant and is therefore not suitable for outdoor applications.

The usage instructions are recommendations based on the tests we have conducted and our experience; carry out your own tests before each application. Due to the large number of applications and storage and processing conditions, we do not assume any liability for a specific application result. Insofar as our free customer service provides technical information or acts as an advisory service, no responsibility is assumed by this service except where the advice or information given falls within the scope of our specified, contractually agreed service or the advisor was acting deliberately. We guarantee consistent quality of our products. We reserve the right to make technical changes and further develop products.