

Conforms to Regulation (EC) No. 1907/2006 (REACH), Annex II, as amended by Regulation (EU) No. 2020/878 - Europe

### SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1 Product identifier

Product name : Hempel's Ecopower Racing 76460  
Product identity : 7646010000, 001345B5  
Product type : bottom paint

#### 1.2 Relevant identified uses of the substance or mixture and uses advised against

Field of application : yacht, ships and shipyards.  
Identified uses : Consumer applications, Professional applications, Used by spraying.  
Spraying - For professional users only.

#### 1.3 Details of the supplier of the safety data sheet

Company details : HEMPEL A/S  
Lundtoftegårdsvej 91  
DK-2800 Kgs. Lyngby  
Denmark  
Tel.: + 45 45 93 38 00  
hempel@hempel.com  
Date of issue : 5 May 2025  
Date of previous issue : 9 December 2024.

#### 1.4 Emergency telephone number

Emergency telephone number (with hours of operation)  
  
+45 45 93 38 00 (08.00 - 17.00)  
See section 4 First aid measures.

### SECTION 2: Hazards identification

#### 2.1 Classification of the substance or mixture

Product definition : Mixture

##### Classification according to Regulation (EC) No. 1272/2008 [CLP/GHS]

Flam. Liq. 3, H226	FLAMMABLE LIQUIDS
Carc. 2, H351	CARCINOGENICITY
STOT SE 3, H335	SPECIFIC TARGET ORGAN TOXICITY (SINGLE EXPOSURE) (Respiratory tract irritation)
STOT SE 3, H336	SPECIFIC TARGET ORGAN TOXICITY (SINGLE EXPOSURE) (Narcotic effects)
Aquatic Chronic 2, H411	AQUATIC HAZARD (LONG-TERM)

See Section 11 for more detailed information on health effects and symptoms.

#### 2.2 Label elements

Hazard pictograms :



Signal word : Warning

Hazard statements :  
H226 - Flammable liquid and vapor.  
H335 - May cause respiratory irritation.  
H336 - May cause drowsiness or dizziness.  
H351 - Suspected of causing cancer.  
H411 - Toxic to aquatic life with long lasting effects.

Precautionary statements :

General : Keep out of reach of children. If medical advice is needed, have product container or label at hand.  
Prevention : Obtain special instructions before use. Wear protective gloves, protective clothing, eye protection, face protection, or hearing protection. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Use only outdoors or in a well-ventilated area. Avoid release to the environment. Avoid breathing vapor.  
Response : Collect spillage. IF exposed or concerned: Get medical advice or attention. IF INHALED: Call a POISON CENTER or doctor if you feel unwell.  
Storage : Store locked up. Store in a well-ventilated place. Keep container tightly closed.  
Disposal : Dispose of contents and container in accordance with all local, regional, national and international regulations.  
Hazardous ingredients : Solvent naphtha (petroleum), light arom.  
4-methylpentan-2-one

### SECTION 2: Hazards identification

Supplemental label elements : Repeated exposure may cause skin dryness or cracking.  
Contains 2,5-di-tert-butylhydroquinone. May produce an allergic reaction.  
Warning! Hazardous respirable droplets may be formed when sprayed. Do not breathe spray or mist.

#### Special packaging requirements

Containers to be fitted with child-resistant fastenings : Not applicable.

Tactile warning of danger : Yes, applicable.

### 2.3 Other hazards

This mixture does not contain any substances that are assessed to be a PBT or a vPvB.

Other hazards which do not result in classification : None known.

### SECTION 3: Composition/information on ingredients

#### 3.2 Mixtures

Product/ingredient name	Identifiers	%	Regulation (EC) No. 1272/2008 [CLP]	Type
Solvent naphtha (petroleum), light arom.	REACH #: 01-2119455851-35 EC: 918-668-5 CAS: 128601-23-0	≥25 - ≤50	Flam. Liq. 3, H226 STOT SE 3, H335 STOT SE 3, H336 Asp. Tox. 1, H304 Aquatic Chronic 2, H411 EUH066	[1]
titanium dioxide	REACH #: 01-2119489379-17 EC: 236-675-5 CAS: 13463-67-7 Index: 022-006-00-2	≥10 - ≤25	Carc. 2, H351 (inhalation)	[1] [*]
4-methylpentan-2-one	REACH #: 01-2119473980-30 EC: 203-550-1 CAS: 108-10-1 Index: 606-004-00-4	≥1 - ≤3	Flam. Liq. 2, H225 Acute Tox. 4, H332 Eye Irrit. 2, H319 Carc. 2, H351 STOT SE 3, H336 EUH066	ATE [Inhalation (vapours)] = 11 mg/l [1] [2]
oleic acid, compound with (Z)-N-octadec-9-enylpropane-1,3-diamine (2:1)	REACH #: 01-2119974119-29 EC: 251-846-4 CAS: 34140-91-5	<1	Skin Irrit. 2, H315 Eye Irrit. 2, H319 STOT RE 2, H373 (oral) Aquatic Acute 1, H400 Aquatic Chronic 2, H411	M [Acute] = 10 [1]
2,5-di-tert-butylhydroquinone	REACH #: 01-2120766295-46 EC: 201-841-8 CAS: 88-58-4	≤0.3	Acute Tox. 3, H301 Skin Sens. 1B, H317 STOT SE 3, H335 STOT RE 2, H373 Aquatic Acute 1, H400 Aquatic Chronic 1, H410	ATE [Oral] = 100 mg/kg M [Acute] = 10 M [Chronic] = 10 [1]
trimethylolpropane	REACH #: 01-2119486799-10 EC: 201-074-9 CAS: 77-99-6	≤0.3	Repr. 2, H361fd	- [1]
(Z)-N-9-octadecenylpropane-1,3-diamine	EC: 230-528-9 CAS: 7173-62-8	≤0.083	Acute Tox. 4, H302 Skin Corr. 1B, H314 Eye Dam. 1, H318 STOT RE 1, H372 Aquatic Acute 1, H400 Aquatic Chronic 1, H410	ATE [Oral] = 500 mg/kg M [Acute] = 10 M [Chronic] = 1 [1]
See Section 16 for the full text of the H statements declared above.				

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment and hence require reporting in this section.

#### Type

[1] Substance classified with a health or environmental hazard

[2] Substance with a workplace exposure limit, see section 8.

[\*] The classification as a carcinogen by inhalation applies only to mixtures placed on the market in powder form containing 1% or more of titanium dioxide particles with aerodynamic diameter ≤ 10 µm not bound within a matrix.

### SECTION 4: First aid measures

#### 4.1 Description of first aid measures

General :	In all cases of doubt, or when symptoms persist, seek medical attention. Never give anything by mouth to an unconscious person. If breathing is irregular, drowsiness, loss of consciousness or cramps: Call 112 and give immediate treatment (first aid).
Eye contact :	Check for and remove any contact lenses. Immediately flush eyes with plenty of water for at least 15 minutes, occasionally lifting the upper and lower eyelids. Seek immediate medical attention/advice.
Inhalation :	Remove to fresh air and keep at rest in a position comfortable for breathing. Give nothing by mouth. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel. If unconscious, place in recovery position and get medical attention immediately.
Skin contact :	Wash skin thoroughly with soap and water or use recognized skin cleanser. Do NOT use solvents or thinners. Remove contaminated clothing and shoes.
Ingestion :	If swallowed, seek medical advice immediately and show this container or label. Keep person warm and at rest. Do not induce vomiting unless directed to do so by medical personnel. Lower the head so that vomit will not re-enter the mouth and throat.
Protection of first-aiders :	No action shall be taken involving any personal risk or without suitable training. If it is suspected that fumes are still present, the rescuer should wear an appropriate mask or self-contained breathing apparatus. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation.

#### 4.2 Most important symptoms and effects, both acute and delayed

##### Potential acute health effects

Eye contact :	No known significant effects or critical hazards.
Inhalation :	Can cause central nervous system (CNS) depression. May cause drowsiness or dizziness. May cause respiratory irritation.
Skin contact :	Defatting to the skin. May cause skin dryness and irritation.
Ingestion :	Can cause central nervous system (CNS) depression.

##### Over-exposure signs/symptoms

Eye contact :	No specific data.
Inhalation :	Adverse symptoms may include the following: respiratory tract irritation coughing nausea or vomiting headache drowsiness/fatigue dizziness/vertigo unconsciousness
Skin contact :	Adverse symptoms may include the following: irritation dryness cracking
Ingestion :	No specific data.

#### 4.3 Indication of any immediate medical attention and special treatment needed

Notes to physician :	Treat symptomatically. Contact poison treatment specialist immediately if large quantities have been ingested or inhaled.
Specific treatments :	No specific treatment.

### SECTION 5: Firefighting measures

#### 5.1 Extinguishing media

Extinguishing media :	Recommended: alcohol resistant foam, CO <sub>2</sub> , powders, water spray. Not to be used: waterjet.
-----------------------	---

#### 5.2 Special hazards arising from the substance or mixture

Hazards from the substance or mixture :	Flammable liquid and vapor. Runoff to sewer may create fire or explosion hazard. In a fire or if heated, a pressure increase will occur and the container may burst, with the risk of a subsequent explosion. This material is toxic to aquatic life with long lasting effects. Fire water contaminated with this material must be contained and prevented from being discharged to any waterway, sewer or drain.
---	--

### SECTION 5: Firefighting measures

Hazardous combustion products : Decomposition products may include the following materials: carbon oxides metal oxide/oxides

#### 5.3 Advice for firefighters

Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training. Fire will produce dense black smoke. Exposure to decomposition products may cause a health hazard. Cool closed containers exposed to fire with water. Do not release runoff from fire to drains or watercourses. Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode. Clothing for fire-fighters (including helmets, protective boots and gloves) conforming to European standard EN 469 will provide a basic level of protection for chemical incidents.

### SECTION 6: Accidental release measures

#### 6.1 Personal precautions, protective equipment and emergency procedures

Avoid all direct contact with the spilled material. Exclude sources of ignition and be aware of explosion hazard. Ventilate the area. Avoid breathing vapor or mist. Refer to protective measures listed in sections 7 and 8. No action shall be taken involving any personal risk or without suitable training. If the product contaminates lakes, rivers, or sewers, inform the appropriate authorities in accordance with local regulations.

#### 6.2 Environmental precautions

Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air). Water polluting material. May be harmful to the environment if released in large quantities.

#### 6.3 Methods and materials for containment and cleaning up

Stop leak if without risk. Move containers from spill area. Approach release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations (see Section 13). Use spark-proof tools and explosion-proof equipment. Contaminated absorbent material may pose the same hazard as the spilled product.

#### 6.4 Reference to other sections

See Section 1 for emergency contact information.  
See Section 8 for information on appropriate personal protective equipment.  
See Section 13 for additional waste treatment information.

### SECTION 7: Handling and storage

#### 7.1 Precautions for safe handling

Vapors are heavier than air and may spread along floors. Vapors may form explosive mixtures with air. Prevent the creation of flammable or explosive concentrations of vapors in air and avoid vapor concentrations higher than the occupational exposure limits. In addition, the product should be used only in areas from which all naked lights and other sources of ignition have been excluded. Electrical equipment should be protected to the appropriate standard. To dissipate static electricity during transfer, ground drum and connect to receiving container with bonding strap. No sparking tools should be used.

Avoid inhalation of vapour, dust and spray mist. Avoid contact with skin and eyes. Eating, drinking and smoking should be prohibited in area where this material is handled, stored and processed. Appropriate personal protective equipment: see Section 8. Always keep in containers made from the same material as the original one.

#### 7.2 Conditions for safe storage, including any incompatibilities

Store in accordance with local regulations. Store in a cool, well-ventilated area away from incompatible materials and ignition sources. Keep out of the reach of children. Keep away from: Oxidizing agents, strong alkalis, strong acids. No smoking. Prevent unauthorized access. Containers that are opened must be carefully resealed and kept upright to prevent leakage.

#### 7.3 Specific end use(s)

See separate Product Data Sheet for recommendations or industrial sector specific solutions.

### SECTION 8: Exposure controls/personal protection

#### 8.1 Control parameters

##### Occupational exposure limits

Product/ingredient name	Exposure limit values
4-methylpentan-2-one	<b>EU OEL (Europe, 1/2022)</b> TWA 8 hours: 20 ppm. TWA 8 hours: 83 mg/m <sup>3</sup> . STEL 15 minutes: 50 ppm. STEL 15 minutes: 208 mg/m <sup>3</sup> .

##### Biological exposure indices

Product/ingredient name	Exposure limit values
No exposure limit value known.	

##### Recommended monitoring procedures

Reference should be made to monitoring standards, such as the following: European Standard EN 689 (Workplace atmospheres - Guidance for the assessment of exposure by inhalation to chemical agents for comparison with limit values and measurement strategy) European Standard EN 14042 (Workplace atmospheres - Guide for the application and use of procedures for the assessment of exposure to chemical and biological agents) European Standard EN 482 (Workplace atmospheres - General requirements for the performance of procedures for the measurement of chemical agents) Reference to national guidance documents for methods for the determination of hazardous substances will also be required.

##### Derived effect levels

Not applicable.

##### Predicted effect concentrations

Not applicable.

#### 8.2 Exposure controls

##### Appropriate engineering controls

Arrange sufficient ventilation by local exhaust ventilation and good general ventilation to keep the airborne concentrations of vapors or dust lowest possible and below their respective threshold limit value. Ensure that eyewash stations and safety showers are proximal to the work-station location.

##### Individual protection measures

General :

Gloves must be worn for all work that may result in soiling. Apron/coveralls/protective clothing must be worn when soiling is so great that regular work clothes do not adequately protect skin against contact with the product. Safety eyewear should be used when there is a likelihood of exposure.



Hygiene measures :

Wash hands, forearms, and face thoroughly after handling compounds and before eating, smoking, using lavatory, and at the end of day.

Eye/face protection :

Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists, gases or dusts. If contact is possible, the following protection should be worn, unless the assessment indicates a higher degree of protection: safety glasses with side-shields.

Hand protection :

Wear chemically resistant gloves (tested to EN374) in combination with 'basic' employee training. The quality of the chemical-resistant protective gloves must be chosen as a function of the specific workplace concentrations and quantity of hazardous substances.

Since the actual work situation is unknown. Supplier of gloves should be contacted in order to find the appropriate type. Below listed glove(s) should be regarded as generic advice:

Recommended: Silver Shield / Barrier / 4H gloves, nitrile rubber (>0.3 mm), polyvinyl alcohol (PVA), Viton®

May be used: nitrile rubber (>0.1 mm), butyl rubber (>0.5 mm)

Short term exposure: neoprene rubber (>0.1 mm), natural rubber (latex) (>0.4 mm), polyvinyl chloride (PVC), butyl rubber (>0.3 mm)

Body protection :

Personal protective equipment for the body should be selected based on the task being performed and the risks involved handling this product.

Wear suitable protective clothing. Always wear protective clothing when spraying.

### SECTION 8: Exposure controls/personal protection

Respiratory protection : **When the product is applied by spraying and for continuous or prolonged work always wear an air-fed respirator e.g. hood with supply of fresh or compressed air or a full face, powered air purifying filter. Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator. If working areas have insufficient ventilation: When the product is applied by means that will not generate an aerosol such as, brush or roller wear half or totally covering mask equipped with gas filter of type A, when grinding use particle filter of type P. (EN140) Be sure to use an approved/certified respirator or equivalent.**

#### Environmental exposure controls

Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

### SECTION 9: Physical and chemical properties

#### 9.1 Information on basic physical and chemical properties

Physical state :	Liquid.																					
Color :	White																					
Odor :	Solvent-like																					
pH :	Testing not relevant or not possible due to nature of the product.																					
Melting point/freezing point :	Testing not relevant or not possible due to nature of the product.																					
Boiling point/boiling range :	Testing not relevant or not possible due to nature of the product.																					
Flash point :	Closed cup: 35°C (95°F)																					
Evaporation rate :	Testing not relevant or not possible due to nature of the product.																					
Flammability :	Flammable in the presence of the following materials or conditions: open flames, sparks and static discharge, heat and oxidizing materials. Slightly flammable in the presence of the following materials or conditions: reducing materials.																					
Vapor pressure :	<table><tr><td></td><td colspan="3">Vapor Pressure at 20°C</td><td colspan="3">Vapor pressure at 50°C</td></tr><tr><td>Ingredient name</td><td>mm Hg</td><td>kPa</td><td>Method</td><td>mm Hg</td><td>kPa</td><td>Method</td></tr><tr><td>Solvent naphtha (petroleum), light arom.</td><td>0.8 - 4.6</td><td>0.11 - 0.61</td><td></td><td></td><td></td><td></td></tr></table>		Vapor Pressure at 20°C			Vapor pressure at 50°C			Ingredient name	mm Hg	kPa	Method	mm Hg	kPa	Method	Solvent naphtha (petroleum), light arom.	0.8 - 4.6	0.11 - 0.61				
	Vapor Pressure at 20°C			Vapor pressure at 50°C																		
Ingredient name	mm Hg	kPa	Method	mm Hg	kPa	Method																
Solvent naphtha (petroleum), light arom.	0.8 - 4.6	0.11 - 0.61																				
Vapor density :	Not available.																					
Specific gravity :	1.27 g/cm³																					
Partition coefficient (LogKow) :	Testing not relevant or not possible due to nature of the product.																					
Auto-ignition temperature :	<table><tr><td>Ingredient name</td><td>°C</td><td>°F</td><td>Method</td></tr><tr><td>Solvent naphtha (petroleum), light arom.</td><td>280 - 470</td><td>536 - 878</td><td></td></tr></table>	Ingredient name	°C	°F	Method	Solvent naphtha (petroleum), light arom.	280 - 470	536 - 878														
Ingredient name	°C	°F	Method																			
Solvent naphtha (petroleum), light arom.	280 - 470	536 - 878																				
Decomposition temperature :	Testing not relevant or not possible due to nature of the product.																					
Viscosity :	Aspiration hazard (H304) Not classified. Testing not relevant due to nature of the product.																					
Explosive properties :	Slightly explosive in the presence of the following materials or conditions: open flames, sparks and static discharge and heat.																					
Oxidizing properties :	Testing not relevant or not possible due to nature of the product.																					

#### 9.2 Other information

Solvent(s) % by weight :	Weighted average: 35 %
Water % by weight :	Weighted average: 0 %
VOC content :	<b>450.9 g/l</b>
TOC Content :	<b>Weighted average: 399 g/l</b>
Solvent Gas :	Weighted average: 0.096 m <sup>3</sup> /l



### SECTION 10: Stability and reactivity

#### 10.1 Reactivity

No specific test data related to reactivity available for this product or its ingredients.

#### 10.2 Chemical stability

The product is stable.

#### 10.3 Possibility of hazardous reactions

Under normal conditions of storage and use, hazardous reactions will not occur.

#### 10.4 Conditions to avoid

Avoid all possible sources of ignition (spark or flame). Do not pressurize, cut, weld, braze, solder, drill, grind or expose containers to heat or sources of ignition.

#### 10.5 Incompatible materials

Highly reactive or incompatible with the following materials: reducing materials.

Reactive or incompatible with the following materials: oxidizing materials.

#### 10.6 Hazardous decomposition products

When exposed to high temperatures (i.e. in case of fire) harmful decomposition products may be formed:

Decomposition products may include the following materials: carbon oxides metal oxide/oxides

### SECTION 11: Toxicological information

#### 11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

Exposure to component solvent vapor concentrations may result in adverse health effects such as mucous membrane and respiratory system irritation and adverse effects on the kidneys, liver and central nervous system. Solvents may cause some of the above effects by absorption through the skin. Symptoms and signs include headaches, dizziness, fatigue, muscular weakness, drowsiness and, in extreme cases, loss of consciousness. Repeated or prolonged contact with the preparation may cause removal of natural fat from the skin, resulting in non-allergic contact dermatitis and absorption through the skin. If splashed in the eyes, the liquid may cause irritation and reversible damage. Accidental swallowing may cause stomach pain. Chemical lung inflammation may occur if the product is taken into the lungs via vomiting.

#### Acute toxicity

Product/ingredient name	Result	Dose / Exposure	Effects
Solvent naphtha (petroleum), light arom.	Rat - Oral - LD50	3492 mg/kg	Toxic effects: Behavioral - Somnolence (general depressed activity) Lung, Thorax, or Respiration - Dyspnea Lung, Thorax, or Respiration - Respiratory depression
titanium dioxide	Rabbit - Dermal - LD50	3160 mg/kg	
	Rat - Inhalation - LC50 Vapor	6193 mg/m <sup>3</sup> [4 hours]	
	Rat - Oral - LD50	>5000 mg/kg	
	Rabbit - Dermal - LD50	>5000 mg/kg	
	Rat - Inhalation - LC50 Dusts and mists	>6.8 mg/l [4 hours]	
4-methylpentan-2-one	Rabbit - Dermal - LD	>3 g/kg	
	Rat - Inhalation - LC50 Vapor	11 mg/l [4 hours]	
2,5-di-tert-butylhydroquinone	Rat - Dermal - LD50	>4000 mg/kg	
trimethylolpropane	Rat - Oral - LD50	50 - 300 mg/kg	
	Rat - Oral - LD50	14100 mg/kg	

#### Acute toxicity estimates

Product/ingredient name	Oral mg/kg	Dermal mg/kg	Inhalation (gases) ppm	Inhalation (vapors) mg/l	Inhalation (dusts and mists) mg/l
Hempel's Ecopower Racing 76460	50429.3			482.4	
Solvent naphtha (petroleum), light arom.	3492	3160			
4-methylpentan-2-one				11	
2,5-di-tert-butylhydroquinone	100				
trimethylolpropane	14100				
(Z)-N-9-octadecenylpropane-1,3-diamine	500				

#### Irritation/Corrosion

### SECTION 11: Toxicological information

Product/ingredient name	Result	Species	Exposure
Solvent naphtha (petroleum), light arom.	Rabbit - Eyes - Mild irritant	Duration of treatment/ exposure: 24 hours	Amount/concentration applied: 100 microliters
titanium dioxide	Rabbit - Respiratory - Mild irritant Rabbit - Skin - Moderate irritant Human - Skin - Mild irritant	Duration of treatment/ exposure: 72 hours	Amount/concentration applied: 300 Micrograms Intermittent
4-methylpentan-2-one	Rabbit - Eyes - Moderate irritant Rabbit - Skin - Mild irritant	Duration of treatment/ exposure: 24 hours Duration of treatment/ exposure: 24 hours	Amount/concentration applied: 100 microliters Amount/concentration applied: 500 milligrams

#### Sensitizer

Product/ingredient name	Species - Route of exposure	Result
2,5-di-tert-butylhydroquinone	Mouse - skin	Result: Sensitizing

#### Mutagenic effects

No known data available in our database.

#### Carcinogenicity

No known data available in our database.

#### Reproductive toxicity

No known data available in our database.

#### Specific target organ toxicity (single exposure)

Product/ingredient name	Category	Route of exposure	Target organs
Solvent naphtha (petroleum), light arom.	Category 3		Respiratory tract irritation
4-methylpentan-2-one	Category 3		Narcotic effects
2,5-di-tert-butylhydroquinone	Category 3		Narcotic effects Respiratory tract irritation

#### Specific target organ toxicity (repeated exposure)

Product/ingredient name	Category	Route of exposure	Target organs
oleic acid, compound with (Z)-N-octadec-9-enylpropane-1,3-diamine (2:1)	Category 2	oral	-
2,5-di-tert-butylhydroquinone	Category 2	-	-
(Z)-N-9-octadecenylpropane-1,3-diamine	Category 1	-	-

#### Aspiration hazard

Product/ingredient name	Result
Solvent naphtha (petroleum), light arom.	ASPIRATION HAZARD - Category 1

#### Information on the likely routes of exposure

Routes of entry anticipated: Oral, Dermal, Inhalation.

#### Potential chronic health effects

No known significant effects or critical hazards.

#### 11.2 Information on other hazards

Endocrine disrupting properties : The product does not meet the criteria to be considered as having endocrine disrupting properties according to the criteria set out in either Regulation (EC) No. 1907/2006 or Regulation (EC) No 1272/2008.

Other information : No additional known significant effects or critical hazards.



### SECTION 12: Ecological information

#### 12.1 Toxicity

Do not allow to enter drains or watercourses. Toxic to aquatic life with long lasting effects.

Product/ingredient name	Result	Species	Exposure
Solvent naphtha (petroleum), light arom.	Acute - LC50	Fish - <i>Oncorhynchus mykiss</i> (rainbow trout)	9.22 mg/l [96 hours]
	Acute - EC50	Algae - <i>Pseudokirchneriella subcapitata</i> (green algae)	2.6 mg/l [96 hours]
titanium dioxide	Acute - EC50	Daphnia	3.2 mg/l [48 hours]
	Acute - LC50	Fish	>100 mg/l [96 hours]
4-methylpentan-2-one	Acute - LC50	Daphnia	>100 mg/l [48 hours]
	Chronic - NOEC - Fresh water	Daphnia - Water flea - <i>Daphnia magna</i>	7800 - 39000 µg/l [21 days]
	Chronic - NOEC - Fresh water	Fish - Fathead minnow - <i>Pimephales promelas</i> - Embryo	168 mg/l [33 days]
oleic acid, compound with (Z)-N-octadec-9-enylpropane-1,3-diamine (2:1)	Acute - LC50	Fish	0.13 mg/l [96 hours]
2,5-di-tert-butylhydroquinone	Acute - EC50	Algae	0.041 mg/l [72 hours]
	Acute - EC50	Daphnia	0.4 mg/l [48 hours]
	Acute - EC50	Algae	0.038 mg/l [72 hours]
(Z)-N-9-octadecenylpropane-1,3-diamine	Acute - EC50	Algae	0.05 mg/l [72 hours]

#### 12.2 Persistence and degradability

Product/ingredient name	Test	Result
Solvent naphtha (petroleum), light arom.		>70% [28 days] - Readily
	OECD Ready Biodegradability - Manometric Respirometry Test	>60% [28 days] - Readily 78% [28 days] - Readily
4-methylpentan-2-one		84% [14 days]
oleic acid, compound with (Z)-N-octadec-9-enylpropane-1,3-diamine (2:1)	OECD Ready Biodegradability - Closed Bottle Test	66% [28 days] - Readily
trimethylolpropane	OECD Inherent Biodegradability: Zahn-Wellens/EMPA Test	100% [28 days] - Readily
(Z)-N-9-octadecenylpropane-1,3-diamine	OECD Ready Biodegradability - Closed Bottle Test	66% [28 days] - Readily

Product/ingredient name	Aquatic half-life	Photolysis	Biodegradability
Solvent naphtha (petroleum), light arom.			Readily
4-methylpentan-2-one			Readily
oleic acid, compound with (Z)-N-octadec-9-enylpropane-1,3-diamine (2:1)			Readily
trimethylolpropane			Readily
(Z)-N-9-octadecenylpropane-1,3-diamine			Readily

#### 12.3 Bioaccumulative potential

Product/ingredient name	LogP <sub>ow</sub>	BCF	Potential
Solvent naphtha (petroleum), light arom.	-	10 - 2500	High
4-methylpentan-2-one	1.9	2	Low
2,5-di-tert-butylhydroquinone	4.85	440	Low
trimethylolpropane	-0.47	<1	Low
(Z)-N-9-octadecenylpropane-1,3-diamine	0.03	0.5	Low

#### 12.4 Mobility in soil

##### Soil/Water partition coefficient

Product/ingredient name	logK <sub>oc</sub>	K <sub>oc</sub>
4-methylpentan-2-one	1.61	40.9047
2,5-di-tert-butylhydroquinone	3.75	5563.03
trimethylolpropane	1.22	16.5101
(Z)-N-9-octadecenylpropane-1,3-diamine	4.14	13941.9

### SECTION 12: Ecological information

#### Results of PMT and vPvM assessment

Product/ingredient name	PMT	P	M	T	vPvM	vP	vM
Solvent naphtha (petroleum), light arom.	No	No	No	No	No	No	No
titanium dioxide	No	No	No	No	No	No	No
4-methylpentan-2-one	No	No	Yes	No	No	No	Yes
oleic acid, compound with (Z)-N-octadec-9-enylpropane-1,3-diamine (2:1)	No	No	No	Yes	No	No	No
2,5-di-tert-butylhydroquinone	No	No	No	Yes	No	No	No
trimethylolpropane	No	No	Yes	Yes	No	No	Yes
(Z)-N-9-octadecenylpropane-1,3-diamine	No	No	No	Yes	No	No	No

Mobility : The product does not meet the criteria to be considered as a PMT or vPvM.

#### 12.5 Results of PBT and vPvB assessment

##### Regulation (EC) No. 1907/2006 [REACH]

Product/ingredient name	PBT	P	B	T	vPvB	vP	vB
Solvent naphtha (petroleum), light arom.	No	No	No	No	No	No	No
titanium dioxide	No	No	No	No	No	No	No
4-methylpentan-2-one	No	No	No	No	No	No	No
oleic acid, compound with (Z)-N-octadec-9-enylpropane-1,3-diamine (2:1)	No	No	No	Yes	No	No	No
2,5-di-tert-butylhydroquinone	No	No	No	Yes	No	No	No
trimethylolpropane	No	No	No	Yes	No	No	No
(Z)-N-9-octadecenylpropane-1,3-diamine	No	No	No	Yes	No	No	No

##### Regulation (EC) No. 1272/2008 [CLP]

Product/ingredient name	PBT	P	B	T	vPvB	vP	vB
Solvent naphtha (petroleum), light arom.	No	No	No	No	No	No	No
titanium dioxide	No	No	No	No	No	No	No
4-methylpentan-2-one	No	No	No	No	No	No	No
oleic acid, compound with (Z)-N-octadec-9-enylpropane-1,3-diamine (2:1)	No	No	No	Yes	No	No	No
2,5-di-tert-butylhydroquinone	No	No	No	Yes	No	No	No
trimethylolpropane	No	No	No	Yes	No	No	No
(Z)-N-9-octadecenylpropane-1,3-diamine	No	No	No	Yes	No	No	No

Conclusion/Summary : The product does not meet the criteria to be considered as a PBT or vPvB.

#### 12.6 Endocrine disrupting properties

The product does not meet the criteria to be considered as having endocrine disrupting properties according to the criteria set out in either Regulation (EC) No. 1907/2006 or Regulation (EC) No 1272/2008.

#### 12.7 Other adverse effects

No known significant effects or critical hazards.

### SECTION 13: Disposal considerations

#### 13.1 Waste treatment methods

The generation of waste should be avoided or minimized wherever possible. Residues of the product is listed as hazardous waste. Dispose of according to all state and local applicable regulations. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction. Spillage, remains, discarded clothes and similar should be discarded in a fireproof container.

European waste catalogue no. (EWC) is given below.






European waste catalogue (EWC) : 08 01 11\*

#### Packaging

The generation of waste should be avoided or minimized wherever possible. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible.

### SECTION 14: Transport information

Transport may take place according to national regulation or ADR for transport by road, RID for transport by train, IMDG for transport by sea, IATA for transport by air.

	14.1 UN / ID no.	14.2 Proper shipping name	14.3 Transport hazard class(es)	14.4 PG*	14.5 Env*	Additional information
<b>ADR/RID Class</b>	UN1263	PAINT	3  	III	Yes.	The environmentally hazardous substance mark is not required when transported in sizes of ≤5 L or ≤5 kg. <b>Tunnel code</b> (D/E)
<b>IMDG Class</b>	UN1263	PAINT. (Solvent naphtha (petroleum), light arom.)	3  	III	Yes.	The marine pollutant mark is not required when transported in sizes of ≤5 L or ≤5 kg. <b>Emergency schedules</b> F-E, S-E
<b>IATA Class</b>	UN1263	PAINT	3 	III	Yes.	The environmentally hazardous substance mark may appear if required by other transportation regulations.

PG\* : Packing group

Env.\* : Environmental hazards

### 14.6 Special precautions for user

**Transport within user's premises:** always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in the event of an accident or spillage.

### 14.7 Maritime transport in bulk according to IMO instruments

Not applicable.

### SECTION 15: Regulatory information

#### 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

EU Regulation (EC) No. 1907/2006 (REACH) Annex XIV - List of substances subject to authorization - Substances of very high concern

#### Annex XIV

None of the components are listed.

#### Substances of very high concern

None of the components are listed.

Annex XVII - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles

Not applicable.

#### Other EU regulations

**Seveso category** This product is controlled under the Seveso III Directive.

<b>Seveso category</b>
P5c: Flammable liquids 2 and 3 not falling under P5a or P5b E2: Hazardous to the aquatic environment - Chronic 2

#### International regulations

#### IMO Anti-fouling System Convention Compliant (AFS/CONF/26)

This product does not contain organotin compounds acting as biocides and complies with the International Convention on the Control of Harmful Anti-fouling Systems on Ships as adopted by IMO October 2001 (IMO document AFS/CONF/26)

Product type : bottom paint  
 Manufacturer : Hempel A/S  
 Product name and/or code : Hempel's Ecopower Racing 76460  
 7646010000  
 Colour : White

Note: This name is shown on the product container. All products in HEMPEL's containers carrying this name comply with the IMO Convention (AFS/CONF/26).

### SECTION 15: Regulatory information

Active ingredient(s) :

#### 15.2 Chemical Safety Assessment

Not applicable.

### SECTION 16: Other information

Abbreviations and acronyms :

ATE = Acute Toxicity Estimate  
 CLP = Classification, Labelling and Packaging Regulation [Regulation (EC) No. 1272/2008]  
 EUH statement = CLP-specific Hazard statement  
 RRN = REACH Registration Number  
 DNEL = Derived No Effect Level  
 PNEC = Predicted No Effect Concentration

Full text of abbreviated H statements :

H225 Highly flammable liquid and vapor.  
 H226 Flammable liquid and vapor.  
 H301 Toxic if swallowed.  
 H302 Harmful if swallowed.  
 H304 May be fatal if swallowed and enters airways.  
 H314 Causes severe skin burns and eye damage.  
 H315 Causes skin irritation.  
 H317 May cause an allergic skin reaction.  
 H318 Causes serious eye damage.  
 H319 Causes serious eye irritation.  
 H332 Harmful if inhaled.  
 H335 May cause respiratory irritation.  
 H336 May cause drowsiness or dizziness.  
 H351 Suspected of causing cancer.  
 H361fd Suspected of damaging fertility. Suspected of damaging the unborn child.  
 H372 Causes damage to organs through prolonged or repeated exposure.  
 H373 May cause damage to organs through prolonged or repeated exposure.  
 H400 Very toxic to aquatic life.  
 H410 Very toxic to aquatic life with long lasting effects.  
 H411 Toxic to aquatic life with long lasting effects.  
 EUH066 Repeated exposure may cause skin dryness or cracking.

Full text of classifications [CLP/GHS] :

Acute Tox. 3 ACUTE TOXICITY - Category 3  
 Acute Tox. 4 ACUTE TOXICITY - Category 4  
 Aquatic Acute 1 AQUATIC HAZARD (ACUTE) - Category 1  
 Aquatic Chronic 1 AQUATIC HAZARD (LONG-TERM) - Category 1  
 Aquatic Chronic 2 AQUATIC HAZARD (LONG-TERM) - Category 2  
 Asp. Tox. 1 ASPIRATION HAZARD - Category 1  
 Carc. 2 CARCINOGENICITY - Category 2  
 Eye Dam. 1 SERIOUS EYE DAMAGE/ EYE IRRITATION - Category 1  
 Eye Irrit. 2 SERIOUS EYE DAMAGE/ EYE IRRITATION - Category 2  
 Flam. Liq. 2 FLAMMABLE LIQUIDS - Category 2  
 Flam. Liq. 3 FLAMMABLE LIQUIDS - Category 3  
 Repr. 2 TOXIC TO REPRODUCTION - Category 2  
 Skin Corr. 1B SKIN CORROSION/IRRITATION - Category 1B  
 Skin Irrit. 2 SKIN CORROSION/IRRITATION - Category 2  
 Skin Sens. 1B SKIN SENSITIZATION - Category 1B  
 STOT RE 1 SPECIFIC TARGET ORGAN TOXICITY (REPEATED EXPOSURE) - Category 1  
 STOT RE 2 SPECIFIC TARGET ORGAN TOXICITY (REPEATED EXPOSURE) - Category 2  
 STOT SE 3 SPECIFIC TARGET ORGAN TOXICITY (SINGLE EXPOSURE) - Category 3

Procedure used to derive the classification according to Regulation (EC) No. 1272/2008 [CLP/GHS]

Classification	Justification
FLAMMABLE LIQUIDS	On basis of test data
CARCINOGENICITY	Calculation method
SPECIFIC TARGET ORGAN TOXICITY (SINGLE EXPOSURE) (Respiratory tract irritation)	Calculation method
SPECIFIC TARGET ORGAN TOXICITY (SINGLE EXPOSURE) (Narcotic effects)	Calculation method
AQUATIC HAZARD (LONG-TERM)	Calculation method

#### Notice to reader

📌 Indicates information that has changed from previously issued version.

The information contained in this safety data sheet is based on the present state of knowledge and EU and national legislation. It provides guidance on health, safety and environmental aspects for handling the product in a safe way and should not be construed as any guarantee of the technical performance or suitability for particular applications.

It is always the duty of the user/employer to ascertain that the work is planned and carried out in accordance with the national regulations.